

23100 Series

Bearing No.	Dimensions (mm)				Basic Load Rating (KN)	Speed Limit (rpm)	Y	Y	Y
				rs min					
23128KW33C3	140	225	68	2.1	540	895	1200	1800	9.86
23128K	140	225	68	2.1	540	895	1200	1800	9.86
23128	140	225	68	2.1	540	895	1200	1800	10.2
23126W33C3	130	210	64	2	495	795	1300	2000	8.47
23126KW33C3	130	210	64	2	495	795	1300	2000	8.2
23126K	130	210	64	2	495	795	1300	2000	8.2
23126	130	210	64	2	495	795	1300	2000	8.47
23124W33C3	120	200	62	2	455	705	1400	2100	7.7
23124KW33C3	120	200	62	2	455	705	1400	2100	7.46
23124K	120	200	62	2	455	705	1400	2100	7.46
23124	120	200	62	2	455	705	1400	2100	7.7
23122W33C3	110	180	56	2	370	580	1500	2400	5.4
23122KW33C3	110	180	56	2	370	580	1500	2400	5.22
23122K	110	180	56	2	370	580	1500	2400	5.22
23122	110	180	56	2	370	580	1500	2400	5.4
23120W33C3	100	165	52	2	310	470	1700	2600	4.3
23120KW33C3	100	165	52	2	310	470	1700	2600	4.16
23120	100	165	52	2	310	470	1700	2600	4.3
23120K	100	165	52	2	310	470	1700	2600	4.16
23148K	240	400	128	4	1730	3050	650	1000	63.8
23148KW33C3	240	400	128	4	1730	3050	650	1000	63.8
23148W33C3	240	400	128	4	1730	3050	650	1000	65.8
23152	260	440	144	4	2140	3850	600	920	91.4
23152K	260	440	144	4	2140	3850	600	920	88.6
23152KW33C3	260	440	144	4	2140	3850	600	920	88.6
23152W33C3	260	440	144	4	2140	3850	600	920	91.4
23156	280	460	146	5	2300	4250	550	850	97.7

23100 Series

23156K	280	460	146	5	2300	4250	550	850	94.6
23156KW33C3	280	460	146	5	2300	4250	550	850	94.6
23156W33C3	280	460	146	5	2300	4250	550	850	97.7