

24000 Series

Bearing No.	Dimensions (mm)				Basic Load Rating (KN)	Speed Limit (rpm)	Y ₂	Y ₃	Y ₄
	rs	min	Cor	Grease					
24038K30W33C3	190	290	100	2.1	995	1850	900	1400	23.9
24038W33C3	190	290	100	2.1	995	1850	900	1400	24.3
24040	200	310	109	2.1	1160	2140	850	1300	31
24040K30	200	310	109	2.1	1160	2140	850	1300	30.5
24040K30W33C3	200	310	109	2.1	1160	2140	850	1300	30.5
24040W33C3	200	310	109	2.1	1160	2140	850	1300	31
24044	220	340	118	3	1350	2570	770	1200	40.2
24044K30	220	340	118	3	1350	2570	770	1200	39.6
24044K30W33C3	220	340	118	3	1350	2570	770	1200	39.6
24044W33C3	220	340	118	3	1350	2570	770	1200	40.2
24048	240	360	118	3	1410	2770	700	1100	43
24048K30	240	360	118	3	1410	2770	700	1100	42.3
24048K30W33C3	240	360	118	3	1410	2770	700	1100	42.3
24048W33C3	240	360	118	3	1410	2770	700	1100	43
24052	260	400	140	4	1830	3550	640	980	65.2
24052K30	260	400	140	4	1830	3550	640	980	64.1
24052K30W33C3	260	400	140	4	1830	3550	640	980	64.1
24052W33C3	260	400	140	4	1830	3550	640	980	65.2
24056	280	420	140	4	1950	3950	590	900	69
24056K30	280	420	140	4	1950	3950	590	900	67.9
24056K30W33C3	280	420	140	4	1950	3950	590	900	67.9
24056W33C3	280	420	140	4	1950	3950	590	900	69
24060	300	460	160	4	2450	4950	540	840	98
24060K30	300	460	160	4	2450	4950	540	840	96.4
24060K30W33C3	300	460	160	4	2450	4950	540	840	96.4
24060W33C3	300	460	160	4	2450	4950	540	840	98