

Inch Tapered Roller Bearing

Bearing No.	Boundary dimensions mm							Basic load ratings(kN)	
	R							Dynamic(Cr)	Static(Cor)
HM88542/2/510/2/QCL7C	31,750	73,025	29,370	81,5	95	10,4	7500	10000	0,62
M88048/2/010/2/QCL7C	33,338	68,262	22,225	63	69,5	7,8	8000	11000	0,38
14131/14276/Q	33,338	69,012	19,845	53,9	67	7,35	7500	11000	0,35
LM48548/510/Q	34,925	65,088	18,034	54	57	6,2	8500	11000	0,25
LM48548A/510/Q	34,925	65,088	18,034	54	57	6,2	8500	11000	0,25
14137A/14276/Q	34,925	69,012	19,845	53,9	67	7,35	7500	11000	0,34
HM88649/2/610/2/QCL7C	34,925	72,233	25,400	78	90	10	7500	10000	0,50
25877/2/25821/2/Q	34,925	73,025	23,812	72,1	88	9,8	7000	10000	0,47
23690/23620/QCL7C	34,925	73,025	26,988	88	93	10,4	8000	10000	0,52
31594/31520/Q	34,925	76,200	29,370	85,8	106	12	6700	10000	0,63
HM89446/2/410/2/QCL7C	34,925	76,200	29,370	90	106	11,8	7000	9500	0,66
L68149/110/Q	34,988	59,131	15,875	38	44	4,5	9000	12000	0,17
L68149/111/Q	34,988	59,974	15,875	38	44	4,5	9000	12000	0,17
25880/25820/Q	36,487	73,025	23,812	83	88	9,8	8000	10000	0,45
HM89449/2/410/2/QCL7C	36,512	76,200	29,370	90	106	11,8	7000	9500	0,64
LM29748/710/Q	38,100	65,088	18,034	50	57	6,1	8000	11000	0,25
LM29749/710/QCL7CVA607	38,100	65,088	18,034	50	57	6,1	8000	11000	0,25
LM29749/711/Q	38,100	65,088	19,812	50	57	6,1	8000	11000	0,25
LM29749/711/QCL7CVA607	38,100	65,088	19,812	50	57	6,1	8000	11000	0,25
16150/16284/Q	38,100	72,238	20,638	56	60	6,55	8000	10000	0,39
16150/16283/Q	38,100	72,238	23,812	56	60	6,55	8000	10000	0,39
2788/2720/QCL7C	38,100	76,200	23,812	86,5	93	10,4	7500	10000	0,50
3490/3420/QCL7CVQ492	38,100	79,375	29,370	104	110	12,5	7000	9500	0,67
HM801346/310/Q	38,100	82,550	29,370	100	118	13,4	6700	8500	0,78
HM801346X/2/310/QVQ523	38,100	82,550	29,370	100	118	13,4	6700	8500	0,77
418/414/Q	38,100	88,500	26,988	101	114	13,2	6300	9000	0,83
M201047/011/Q	39,688	73,025	25,654	76,5	86,5	9,3	7500	10000	0,45
LM300849/811/Q	40,988	67,975	17,500	50	58,5	6,3	8000	10000	0,24
LM501349/310/Q	41,275	73,431	19,558	63	68	7,65	7500	10000	0,33
LM501349/2/310/2/QCL7C	41,275	73,431	19,558	63	68	7,65	7500	10000	0,33